

Technical Data Sheet

OrangeJET SpotMe White PVC

Product Description

Our orangeJet SpotMe White made of high-quality, white PVC is our solution for all POS shop window wrapping when applied by non-professionals. The bonding is easy-peasy and can really be applied by anyone. The punctual application of the adhesive allows bubble-free application and repositioning. Removal is also child's play and residue-free. A special feature is that the adhesive spots are almost invisible. Made of high-quality PVC and printable with all digital printing technologies.

Application

White window decoration film with adhesive spots (dots) for easy application

Material

PVC calendered

Application Temperature

>10°C / >50°F

Colour / Finish

white / semi-matt

Temperature Resistance

-30°C - +60°C / -22°F - +140°F

Thickness (without liner and adhesive, ISO 4593)

100 µm

Dimensional Stability (FINAT TM 14)

Shrinkage ≤ 1 mm

Adhesive

solvent polyacrylate, clear, removable

Outdoor Durability

6 months

Adhesive Power (FINAT TM 1)

2 N/25 mm (Initial Tac 1 N/25 mm)

Indoor Durability

24 months

Release Paper

Double-Side PE Liner, 140g

Shelf Life / Storage Conditions

18 months in original packaging

Printability

solvent, eco-solvent, latex, UV-gel, UV-cured

18°C - 25°C / 64°F - 77°F, 40 - 60 % relative humidity

Certificates

EN13501 flame-retardant

The published information concerning our products is based on practical knowledge and experience. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. The purchaser must assume all risks for any use, operation and application of the material. We are liable for damage only up to the amount of the purchase price under exclusion of indirect and accidental damage. All information given serves only to describe the product and is not to be regarded as assured properties in the legal sense. Specifications subject to change without notice, errors and omissions excepted.

Technisches Datenblatt

OrangeJET SpotMe White PVC

Produktbeschreibung

Unser orangeJet SpotMe White aus hochwertigem und weißem PVC ist unsere Lösung für alle Schaufensterverklebungen am POS durch nicht professionelle Verkleber. Die Verklebung ist easy-peasy und kann wirklich durch Jedermann aufgebracht werden. Der punktförmige Auftrag des Klebers ermöglicht einen blasenfreien Auftrag und eine Repositionierung. Auch das Entfernen ist kinderleicht und rückstandsfrei. Dabei ist ein besonderes Merkmal, dass die Klebespots nahezu unsichtbar sind.

Anwendung

Weißer Film zur Dekoration auf Fensterscheiben mit Punkt-Kleber (Dot)

Material

PVC kalandriert

Verarbeitungstemperatur

>10°C / >50°F

Farbe / Oberfläche

weiß / seidenmatt

Temperaturbeständigkeit

-30°C - +60°C / -22°F - +140°F

Dicke (ohne Liner und Klebstoff, ISO 4593)

100 µm

Formbeständigkeit (FINAT TM 14)

Schrumpf ≤ 1 mm

Haftklebstoff

Solvent Polyacrylat, transparent, ablösbar

Haltbarkeit im Außenbereich

6 Monate

Klebkraft (FINAT TM 1)

2 N/25 mm (Initial Tac 1 N/25 mm)

Haltbarkeit im Innenbereich

24 Monate

Abdeckung/Liner

Double-Side PE Liner, 140g

Lagerzeit / Lagerbedingungen

18 Monate in Originalverpackung

Bedruckbarkeit

solvent, eco-solvent, Latex, UV-Gel, UV-härtend

18°C - 25°C / 64°F - 77°F, 40 - 60 % relative Luftfeuchtigkeit

Zertifikate

EN13501 flame-retardant

Diese technischen Informationen wurden auf Basis des neuesten Standes der Technik und unserer Erfahrungen zusammengestellt. Aufgrund der Vielzahl der Parameter und Bedingungen, unter denen das beschriebene Produkt eingesetzt wird, ist jeder Anwender verpflichtet, das Produkt in eigener Verantwortung auf die Eignung für den vorgesehenen Verwendungszweck fachgerecht zu prüfen. Eine rechtlich verbindliche Zusicherung bestimmter Eigenschaften kann aus unseren Angaben nicht abgeleitet werden. Haftungsansprüche können maximal für den Beschaffungspreis geltend gemacht werden, indirekte Schäden sowie Unfallschäden sind ausgeschlossen. Irrtümer und Änderungen vorbehalten. Bei Erscheinen einer neueren Version verliert diese Version ihre Gültigkeit.